

<b>CABLE SPECIFICATION</b>					
<p><b>OPTICAL FIBER CABLES</b></p> <ul style="list-style-type: none"> <li>• Single colored tight buffer fiber</li> <li>• High modulus (self-supporting) strength member</li> <li>• Good-performance sheath materials</li> </ul> <p><b>APPLICATION</b></p> <ul style="list-style-type: none"> <li>• Both indoor and outdoor cabling</li> <li>• Suitable for aerial dropping</li> </ul> <p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• Able to be terminated onsite</li> <li>• Flexibility, light weight and compact structure</li> <li>• Easy for stripping, and splicing, simplified installation and maintenance</li> <li>• Low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property</li> <li>• Excellent mechanical performance and free to be customization</li> </ul>					
<b>FIBER</b>					
<b>Type</b>	ITU-T G.657A				
<b>CABLE</b>					
<b>Spec</b>	<b>Outside diameter ( mm )</b>	<b>Max. tensile load (N)</b>		<b>Crush resistant(N/10cm)</b>	
		<b>Short term</b>	<b>Long term</b>	<b>Short term</b>	<b>Long term</b>
GJFJH-1	2.5	150	80	1500	700

GJFJH-1	3.0	200	100		
GJYFJH-1	3.0	500	250		
GJYFJCH-1	3.0 - 5.3	600	300	2200	1000

**SHEATH**

**Inner** According to customer's request, the materials can adopt LSZH, ect.

**Outer** According to customer's request, the materials can adopt LSZH, ect.

**TEMPERATURE RANGE**

<b>Operating</b>	<b>Transportation &amp; Storage</b>	<b>Installation</b>
-20°C~+60°C	-20°C~+60°C	-10°C~+50°C

Remark:

All the values in the table are reference value, subject to the actual customer request.